## P3-DS304-HR

# PT100 Ribbon Temperature Sensor -20°C to +90°C



Sensor with 1.5m 3 core flat PVC ribbon cable

For use with the D3 family of wireless base stations Compatible with a full range of Inteligent Wireless Transmitters (supplied separately)


The sensing element is protected with an industrial grade clear heat shrink measuring only 3mm in diameter and can be used in a wide variety of applications. The thin design of the sensing element provides a fast thermal response.

The sensor is terminated to 3 wire flexible flat ribbon cable providing easy mount through door seals.

Common uses: Fridges | Freezers | Incubators

This product can be supplied with a calibration certificate.

#### **Product Drawing:**



#### **Technical Specifications:**

Temperature Range:20	0°C to 90°C	On Cable Electronics	
Weight: 19 Sensor Cable: 15 Cable Operating Temperature: -20	±0.8°C ±0.3°C 100 Class B	Connector IP Rating:  Connector:  Operating Temperature:  Electronics Sheathing:  Electronics & Probe IP Rating:	_IP67 _3 pin male Hirose 20°C to 55°C _Technomelt OM678 _IP68

#### Compatible P2-WS Wireless Transmitters

Part No. Description
P2-W\$102-0433 - Single Input Wireless Transmitter with Hirose Connector (433Mhz)
P2-W\$103-0433 - Dual Input Wireless Transmitter with Hirose Connectors (433Mhz)
P2-W\$102-2400 - Single Input Wireless Transmitter with Hirose Connector (2.4Ghz)
P2-W\$103-2400 - Dual Input Wireless Transmitter with Hirose Connectors (2.4Ghz)

#### Compatible Accessories

Part No. Description
P7-SA1009 - Probe Fixing Bracket (for pipework, etc)

Doc: 106-10054-01 (DataSheet Inteligent Sensor Range)

### Visit: www.tek-troniks.com Call: 0115 9890090